

Enclosed - Regulated Speed (RS)

Motor Power (kW)	Model	Voltage/Phase		Starter Type	Mounting Config.	Maximum FAD m ³ /min (cfm)			Motor Speed (rpm)	Oil Capacity (litres)	Air Outlet (Rp)	Dimensions (mm)			Noise dB(A)	Weight (kg)	Air Quality (mg/m ³)			
		50Hz	60Hz			6 bar	8 bar	10 bar				Depth	Width	Height						
11.0	HV11RS	400V 3Ph	460V 3Ph	v	Floor	1.74 (61.6)	1.56 (55.0)	1.37 (48.5)	870 to 1900	7.0	¾"	850	700	1550	69	393	<3			
15.0	HV15RS					2.29(80.8)	2.03 (71.6)	1.72 (60.7)	870 to 1800						7.5	1"		70	406	
18.0	HV18RS					2.96 (104.6)	2.75 (96.9)	2.51 (88.5)										507		
22.0	HV22RS					3.53 (124.5)	3.22 (113.8)	3.07 (108.3)		71	520									
30.0	HV30RS					870 to 1700	23.0	1½"	5.38 (189.9)	4.87 (171.9)	4.51 (159.3)				1115	900		1640	73	909
37.0	HV37RS								6.17 (217.8)	5.72 (202.1)	5.27 (186.1)									963
45.0	HV45RS								7.47 (263.7)	6.90 (243.5)	6.51 (230.0)									992
75.0	HV75RS	400V 3Ph	460V 3Ph	v	Floor	11.95 (422.0)	11.04 (390.0)	-	up to 1870	45.0	1½"	955	2330	1600	73	1560	<3			